

1. Unique identification code of the product- **FTP-V U3, FTU-V U3, FTW-V U3, FT_-V/PK/CU/TC/C U3, FTP U3, FTU U3, FTW U3, FT_/PK/CU/TC/C U3, FTP-V P2, FTU-V P2, FTW-V P2, FT_-V/PK/CU/TC/C P2, FTP P2, FTU P2, FTW P2, FT_/PK/CU/TC/C P2**
 type:
2. Intended use/es: **Wooden roof windows intended to be used in domestic and commercial location.**
3. Manufacturer: **FAKRO PP Sp. z o.o.
 ul. Węgierska 144a,
 33-300 Nowy Sącz, Poland
 fakro@fakro.pl**
4. Authorised representative: **./.**
5. System/s of AVCP: **3**
6. Designated standard: **EN 14351-1:2006+A2:2016**
 Approved body/ies: **Centrum stavebního inženýrství a. s. (NB 1390)
 Instytut Techniki Budowlanej (NB 1488)**

7. Declared performance/s:

Essential characteristics	Performance				Designated technical specification
	FTP -V U3 FTU-V U3 FTW-V U3 FT_-V/PK/CU/TC/C U3	FTP U3 FTU U3 FTW U3 FT_/PK/CU/TC/C U3	FTP -V P2 FTU-V P2 FTW-V P2 FT_-V/PK/CU/TC/C P2	FTP P2 FTU P2 FTW P2 FT_/PK/CU/TC/C P2	
7.1 Resistance to wind load	Class C5 (1)	Class C5 (1)	Class C5 (1)	Class C5 (1)	EN 14351-1:2006+A2:2016
7.2 Resistance to snow and permanent load	4H-16-4 (2)	4H-16-4 (2)	4H-15-33.2 (2)	4H-15-33.2 (2)	
7.3 Reaction to fire	D-s2, d2	D-s2, d2	D-s2, d2	D-s2, d2	
7.4 External fire performance	npd (3)	npd (3)	npd (3)	npd (3)	
7.5 Watertightness. Non-shielded (A)	Class E900	Class E900	Class E900	Class E900	
7.6 Impact resistance	Class 3 - 450mm	Class 3 - 450mm	Class 3 - 450mm	Class 3 - 450mm	
7.7 Load-bearing capacity of safety device	Threshold value (350 N)	Threshold value (350 N)	Threshold value (350 N)	Threshold value (350 N)	
7.8 Acoustic performance	32 (-1;-5) [dB]	33 (-1;-5) [dB]	35 (-1;-3) [dB]	36 (-1;-4) [dB]	
7.9 Thermal transmittance	1.3 [W/m ² K] (4)	1.3 [W/m ² K] (4)	1.3 [W/m ² K] (4)	1.3 [W/m ² K] (4)	
Radiation properties:					
7.10 - Solar factor g	0.53	0.53	0.52	0.52	
- Light transmittance	0.76	0.76	0.75	0.75	
7.11 Air permeability	Class 4	Class 4	Class 4	Class 4	

(1) for the windows with the width of > 114 cm and height of > 140 cm: npd, (2) H – external pane toughened, (3) npd – no performance determined, (4) for the reference size (1.14 x 1.40) m – test according to standard EN ISO 12567-2

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above.

Signed on behalf of the manufacturer by:

Ewa Łukaszczyk-Haslik

Nowy Sącz, 03/10/2022

