

1. Unique identification code of the product-type: **FPP-V MAX R1, FPU-V MAX R1, FPW-V MAX R1, FPP MAX R1, FPU MAX R1, FPW MAX R1, FPP-V MAX G61, FPU-V MAX G61, FPW-V MAX G61, FPP MAX G61, FPU MAX G61, FPW MAX G61**
2. Intended use/es: **Wooden roof windows intended to be used in domestic and commercial location.**
3. Manufacturer: **FAKRO PP Sp. z o.o.  
ul. Węgierska 144a,  
33-300 Nowy Sącz, Poland  
fakro@fakro.pl**
4. Authorised representative: **./.**
5. System/s of AVCP: **3**
6. Designated standard: **EN 14351-1:2006+A2:2016**  
 Approved body/ies: **Centrum stavebního inženýrství a. s. (NB 1390)**

## 7. Declared performance/s:

Essential characteristics	Performance				Designated technical specification
	FPP-V MAX R1 FPU-V MAX R1 FPW-V MAX R1	FPP MAX R1 FPU MAX R1 FPW MAX R1	FPP-V MAX G61 FPU-V MAX G61 FPW-V MAX G61	FPP MAX G61 FPU MAX G61 FPW MAX G61	
7.1 Resistance to wind load	Class C3 (1)	Class C3 (1)	Class C3 (1)	Class C3 (1)	EN 14351-1:2006+A2:2016
7.2 Resistance to snow and permanent load	6H-12-33.2 (2)	6H-12-33.2 (2)	6H-12-33.2 (2)	6H-12-33.2 (2)	
7.3 Reaction to fire	npd (3)	npd (3)	npd (3)	npd (3)	
7.4 External fire performance	npd	npd	npd	npd	
7.5 Watertightness. Non-shielded (A)	Class 9A	Class 9A	Class 9A	Class 9A	
7.6 Impact resistance	Class 3 - 450mm	Class 3 - 450mm	Class 3 - 450mm	Class 3 - 450mm	
7.7 Load-bearing capacity of safety device	Threshold value (350 N)	Threshold value (350 N)	Threshold value (350 N)	Threshold value (350 N)	
7.8 Acoustic performance	35 (-1,-3) [dB]	39 (-2,-5) [dB]	35 (-1,-3) [dB]	39 (-2,-5) [dB]	
7.9 Thermal transmittance	1.3 [W/m <sup>2</sup> K] (4)	1.3 [W/m <sup>2</sup> K] (4)	1.3 [W/m <sup>2</sup> K] (4)	1.3 [W/m <sup>2</sup> K] (4)	
7.10 Radiation properties:					
- Solar factor g	0.51	0.51	0.23	0.23	
- Light transmittance	0.75	0.75	0.40	0.40	
7.11 Air permeability	Class 3	Class 3	Class 3	Class 3	

(1) for the windows with the width of > 114 cm and height of > 140 cm: npd, (2) H – external pane toughened, (3) npd – no performance determined, (4) for the reference size (1.14 x 1.40) m – test according to standard EN ISO 12567-2

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above.

Signed on behalf of the manufacturer by:

Ewa Łukaszczyk-Haslik

Nowy Sącz, 03/10/2022

