<b>FAKRO</b> °	Declaration of Performance	No. GH30/UKCA/14351/22
1. Unique identification code of the product-type:	FGH-V P2 Galeria, FGH-V/U P2 Galeria, FGH-	V/W P2 Galeria
2. Intended use/es:	Wooden roof windows intended to be used in domestic and commercial location.	
3. Manufacturer:	FAKRO PP Sp. z o.o. ul. Węgierska 144a, 33-300 Nowy Sącz, Poland fakro@fakro.pl	
4. Authorised representative:	./.	
5. System/s of AVCP:	3	
6. Designated standard: Approved body/ies:	EN 14351-1:2006+A2:2016 Centrum stavebního inženýrství a. s. (NB 1390)	

7. Declared performance/s:

Essential characteristics		Performance	
		FGH-V P2 Galeria FGH-V/U P2 Galeria FGH-V/W P2 Galeria	Designated technical specification
7.1 R	esistance to wind load	Class C5 (1)	
7.2 R	esistance to snow and permanent load	4H-14-33.2 (2)	
7.3 R	eaction to fire	D-s2, d2	
7.4 E	external fire performance	npd (3)	)16
7.5 W	Vatertightness. Non-shielded (A)	Class E900	EN 14351-1:2006+A2:2016
7.6 Ir	mpact resistance	Class 3 - 450mm	
7.7 L	oad-bearing capacity of safety device	Threshold value (350 N)	-1:2006
7.8 A	coustic performance	35 (-1;-3) [dB]	351
7.9 T	hermal transmittance	$1,5 [W/m^2K] (4)$	114
R	adiation properties:		E
7.10 _	Solar factor g	0,52	
-	Light transmittance	0,75	-
7.11 A	ir permeability	Class 3	

Instytut Techniki Budowlanej (NB 1488)

(1) for the windows with the width of > 94 cm and height of > 255 cm: npd, (2) H – external pane toughened, (3) npd – no performance determined, (4) size 94x255 cm – calculation according to standard PN-EN ISO 10077-1, p. 6

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above.

Signed on behalf of the manufacturer by:

Ewa Łukaszczyk-Haslik

Nowy Sacz, 03/10/2022