

1. Unique identification code of the product-type: **FGH-V P5 Galeria, FGH-V/U P5 Galeria, FGH-V/W P5 Galeria**
2. Intended use/es: **Wooden roof windows intended to be used in domestic and commercial location.**
3. Manufacturer: **FAKRO PP Sp. z o.o.  
ul. Węgierska 144a,  
33-300 Nowy Sącz, Poland  
fakro@fakro.pl**
4. Authorised representative: **./.**
5. System/s of AVCP: **3**
6. Designated standard: **EN 14351-1:2006+A2:2016**  
 Approved body/ies: **Centrum stavebního inženýrství a. s. (NB 1390)  
Instytut Techniki Budowlanej (NB 1488)**

## 7. Declared performance/s:

Essential characteristics	Performance	Designated technical specification
	FGH-V P5 Galeria FGH-V/U P5 Galeria FGH-V/W P5 Galeria	
7.1 Resistance to wind load	Class C4 (1)	EN 14351-1:2006+A2:2016
7.2 Resistance to snow and permanent load	4H-10-4H-8-33.2 (2)	
7.3 Reaction to fire	D-s2, d2	
7.4 External fire performance	npd (3)	
7.5 Watertightness. Non-shielded (A)	Class E900	
7.6 Impact resistance	Class 3 - 450mm	
7.7 Load-bearing capacity of safety device	Threshold value (350 N)	
7.8 Acoustic performance	34 (-1;-4) [dB]	
7.9 Thermal transmittance	1.1 [W/m <sup>2</sup> K] (4)	
Radiation properties:		
7.10 - Solar factor g	0.48	
- Light transmittance	0.68	
7.11 Air permeability	Class 3	

(1) for the windows with the width of > 94 cm and height of > 255 cm: npd, (2) H – external pane toughened, (3) npd – no performance determined, (4) size 94x255 cm – calculation according to standard PN-EN ISO 10077-1, p. 6

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above.

Signed on behalf of the manufacturer by:

Ewa Łukaszczyk-Haslik

Nowy Sącz, 03/10/2022

