

1. Unique identification code of the product-type: **DMC-C P4 Secure, DMC-C P4/PK, DMC-M P4Secure, DMC-M P4/PK, DXC-C P4 Secure, DXC-C P4/PK, DXC-M P4 Secure, DXC-M P4/PK**
2. Intended use/es: **Roof lights of plastics with upstand intended to be used for daylighting in flat and inclined roofs of buildings.**
3. Manufacturer: **FAKRO PP Sp. z o.o.
ul. Węgierska 144a,
33-300 Nowy Sącz, Poland
fakro@fakro.pl**
4. Authorised representative: **./.**
5. System/s of AVCP: **3**
6. Designated standard: **EN 1873:2005**
 Approved body/ies: **Centrum stavebního inženýrství a. s. (NB 1390),
Centrum Naukowo - Badawcze Ochrony Przeciwpożarowej - Państwowy Instytut
Badawczy (NB 1438),
Instytut Techniki Budowlanej (NB 1488)**

7. Declared performance/s:

Essential characteristics	Performance		Designated technical specification
	DMC-C P4 Secure, DMC-C P4/PK DMC-M P4Secure, DMC-M P4/PK DXC-C P4 Secure, DXC-C P4/PK DXC-M P4 Secure, DXC-M P4/PK		
7.1 Resistance to upward load	UL 1500		EN 1873:2005
7.2 Resistance to downward loads	DL 2500		
7.3 Reaction to fire	B-s2,d0		
7.4 Resistance to fire	npd (1)		
7.5 External fire performance	B _{roof} (t1)		
7.6 Water tightness	pass		
7.7 Impact resistance, small hard body	pass		
7.8 Impact resistance, large soft body	SB 1200		
7.9 Thermal transmittance	1,2 [W/m ² K] (2)		
7.10 Direct airborne sound insulation	35 (-1;-3) [dB]		
7.11 Luminous transmittance	npd		
7.12 Air permeability	Class A3 (DXC-_) Class 4 (DMC-_, DEC-_)		
7.13 Durability	npd		

(1) npd – no performance determined, (2) acc. to EN ISO 12567-2 (dimension 1,2 x 1,2 m)

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above.

Signed on behalf of the manufacturer by:

Ewa Łukaszczyk-Haslik

Nowy Sącz, 03/10/2022

