

1. Unique identification code of the product-type: **XDP**
2. Intended use/es: **Flexible sheets for waterproofing – Underlays for discontinuous roofing to regulate water vapour penetration**
3. Manufacturer: **FAKRO Sp. z o.o.  
ul. Węgierska 144a,  
33-300 Nowy Sącz, Poland  
fakro@fakro.pl**
4. Authorised representative: **./.**
5. System/s of AVCP: **3**
6. Designated standard: **EN 13859-1: 2010**  
Approved body/ies: **Polskie Centrum Badań i Certifikacji S.A. (NB 1434)**
7. Declared performance/s:

Essential characteristics		Performance (applies to high vapour permeable membrane 115)	Designated technical specification
7.1	Reaction to fire	E-d2	EN 13859-1: 2010
7.2	Water tightness	W1	
7.3	Tensile properties: - longitudinal - transverse	230 +60/-80 [N/50mm] 150 +60/-80 [N/50mm]	
	Elongation: - longitudinal - transverse	90 +/-50 [%] 110 +/-50 [%]	
7.4	Resistance to tearing: - longitudinal - transverse	120 +/-50 [N] 160 +/-60 [N]	
7.5	Flexibility at low temperature	-25 [°C]	
7.6	Resistance to artificial ageing: Tensile properties: - longitudinal - transverse	200 +/-80 [N/50mm] 120 +/-80 [N/50mm]	
	Elongation: - longitudinal - transverse	60 +/-40 [%] 80 +/-40 [%]	
	Water tightness	W1	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above.

Signed on behalf of the manufacturer:



Tomasz Cisoń

Nowy Sącz, 03.10.2022