| | FAKRO ° | Dee | claration of Performance | No. X03/UKCA/16069/22 |
|----|---|-----|---|--------------------------|
| 1. | Unique identification code of the product-type: | | XWT Plus | |
| 2. | Intended use/es: | | Products for thermal insulation in construction | |
| 3. | Manufacturer: | | FAKRO Sp. z o.o. ul. Węgierska 144a, 33-300 Nowy Sącz, Poland fakro@fakro.pl | |
| 4. | Authorised representative: | | ./. | |
| 5. | System/s of AVCP: | | 3 | |
| 6. | Designated standard: | | EN 16069: 2012+A1:2015 | |
| | Approved body/ies: | | FIRES (NB 1396), Instytut Techniki Budowl | anej (NB 1488) |

7. Declared performance/s:

| Essential characteristics | | Performance | Designated technical specification |
|---------------------------|---|---|------------------------------------|
| 7.1 | Reaction to fire | Е | |
| 7.2 | Release of hazardous substances into the interior | NPD | |
| 7.3 | Sound absorption coefficient | NPD | - |
| 7.4 | Airborne sound insulation coefficient | NPD | |
| 7.5 | Combustion through continuous incandescence | NPD | |
| 7.6 | Thermal resistance | $\lambda_{\rm D} = 0.041 \ {\rm W/(m \cdot K)}$ | |
| 7.7 | Water permeability | NPD | |
| 7.8 | Water vapour permeability | NPD | EN 16069: 2012+A1:2015 |
| 7.9 | Compressive strength | NPD | |
| 7.10 | Impact noise transmission index (for floors) | NPD | |
| 7.11 | Insulation durability to heat, weather conditions, ageing/degradation | NPD | |
| 7.12 | Compressive strength in case of ageing/degradation | NPD | |
| 7.13 | Resistance to fire, heat, weather conditions, ageing/degradation | NPD | |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above.

Signed on behalf of the manufacturer:

Tomasz Cisoń

Nowy Sącz, 03.10.2022