

Quotation for Mr Smith

Fakro House, Astron Business Park, Hearthcote Road, Swadlincote, Derbyshire, DE11 9DW. Tel: 01283 554755 Fax: 01283 224545 Email: sales@fakroqb.com Web: www.fakro.co.uk

Thursday, 20 November 2014

Quote Reference: 10101/1 for Barn conversion project

Code	Product	Qty	Each	Value
	To supply only the Fakro products detailed below:	-		
	Please Note the below quotation is based on our interpretation of your			
	requirements, Please confirm all sizes and specification before any resulting			
	orders are placed.			
871B05	FTP-V U3 05 78x98 Electro Z-Wave Window	10	£0.00	£0.00
	Centre Pivot Window. FSC Certified. BBA Approved (02/3944).Semi-automatic			
	pressure ventilation V40P to prevent wind gusting. "topSafe" security and safety			
	offering reinforced hinge and keep together with a steel slat to the lower part of			
	the sash to achieve at least class III safety as per EN13049. External aluminium			
	colour reference RAL7022. Natural wood frame. Internal finish 2 layers of clear			
	lacquer. Bottom placed handle with 2 micro opening positions. Glass construction			
	4-16-4mm with 32dB reduction and external tempered glass internal low-E silver			
	oxide coated producing a U-Value of 1.3W/m ² K (glass U-Value 1.1W/m ² K).			
	Roof 15-90° pitch.			
	Electrically operated roof window equipped with the Z-Wave system which is a			
	Wireless radio protocol.			
	Includes remote control and rain sensor.	_	60.00	00.00
850052 84305	ZWK 10 Wall Mounted Radio Transmitter	5	£0.00	£0.00
	868 MHz Electrical,			
	Able to control 10 receivers separately and 231 accessories in groups.	10	CO 00	CO 00
	ELV 05 78x98 Slate Flashing Suitable for 8mm non-interlocking slate. RAL 7022. Roof 15-90° pitch.	10	£0.00	£0.00
80BC05	DXC-C P2 90x90	4	£0.00	£0.00
	Fixed Closed Domed Flat Roof Window is equipped with a double glazed unit	4	£0.00	£0.00
	which has laminated internal glass and is Anti-Burglary P2A Class. The external			
	dome is made of durable polycarbonate. Special coatings on the inner and outer			
	of the dome surface protect against UV radiation. Heat transmittance co-efficient			
	for the whole window is U-Value 1.2W/m²K.			
	Flashing kit types to be confirmed prior to any resulting orders being placed			
Total				$\mathfrak{L}0.00$

Prices quoted are ex VAT and are subject to Fakro GB Limited Standard Terms and Conditions - copies of which are available upon request.

This VAT exclusive quote is valid for 30 days from the date shown above, Fakro reserve the right to amend the quote should the quantities or specification alter in any way from that shown.

In order to acquire the prices shown in this Quotation document the Quotation Reference 10101/1 MUST BE included on the order for the products.

Substantial discounts can be obtained from builders merchants.

This quotation is our interpretation of the products required. ALL details must be checked and confirmed prior to the placing of any resulting order. Fakro GB Ltd accepts no responsibility or liability for any variances found between this document and drawings or details provided to them.

It is the responsibility of the person, or persons, placing the order to ensure the accuracy and suitability of all products concerned. Special care should be taken when placing orders for BESPOKE ITEMS, which cannot be cancelled once confirmed. If amendments are required please request an updated or amended quotation.

Production lead times commence once the final details have been confirmed to us in writing